



- ▶ Use the screw eye to position and secure bundled harnesses with screws, bolts or rivets
- ▶ Fasten bundles, hoses, ducts, etc. to panels or other surfaces
- ▶ Accepts #10 Screw
- ▶ Made from UL approved Nylon 6/6
- ▶ Normal Service Temperature Range: -40°F to 185°F (-40°C to 85°C)
- ▶ Flammability Rating: UL94V-2

Dimensions = Inches

Cat. No.	Tensile Strength (Lbs.)	Length	Width	Max Bundle Dia.	Mtg Hole Dia.	Bag Qty	Master Bag Qty
NATURAL COLOR							
20312	25	3-7/8	.098	.98	1/8"	100	1000
20314	40	6	.144	1.54	3/16"	100	1000
20316	50	8	.164	2.17	3/16"	100	1000
20317	50	12	.187	3.35	1/4"	100	1000
20318	50	14-1/2	.187	4.02	3/16"	100	100
20320	120	15-3/4	.308	4.80	1/4"	100	100
ULTRAVIOLET BLACK							
20332	25	3-7/8	.098	.98	1/8"	100	1000
20334	40	6	.144	1.54	3/16"	100	1000
20336	50	8	.164	2.17	3/16"	100	1000
20337	50	12	.187	3.35	1/4"	100	1000
20338	50	14-1/2	.187	4.02	3/16"	100	100
20340	120	15-3/4	.308	4.80	1/4"	100	100

In-line Nylon Cable Ties



- ▶ Flat head, low profile design for parallel entry of the tie into the head
- ▶ Fixed and flexible two-wedge design provides a low threading force
- ▶ Made from UL approved Nylon 6/6
- ▶ Temperature Rating: -40°F to 185°F (-40°C to 85°C)
- ▶ Flammability Rating: UL 94V-2

Dimensions = Inches

Cat. No.	Tensile Strength (Lbs.)	Length	Width	Max Bundle Dia.	Color	Bag Qty	Master Bag Qty
20378	50	10-1/8	.354	2.91	Natural	100	1000
20379	50	15-1/2	.354	4.61	Natural	100	1000
20380	50	10-1/8	.354	2.91	Black	100	1000
20381	50	15-1/2	.354	4.61	Black	100	1000

Cable Marker Plates



- ▶ Used to mark cable bundles for permanent identification
- ▶ Installed using standard nylon tie wraps
- ▶ A fine tip permanent marker is recommended for markings
- ▶ Manufactured using natural colored nylon 6/6

Dimensions = Inches

Cat. No	Length	Width	Bag Qty	Master Bag Qty
20382	1.00	0.60	10	100
20384	1.70	0.80	10	100
20386	2.40	1.00	10	100
20388	2.50	2.00	10	100
20389	3.50	0.75	10	100