

## Plastic Cable Clips



Fig 1



Fig 2



Fig 3

- ▶ Impact resistant, non-corrosive
- ▶ Complete with corrosion resistant, hardened steel nails for securing cable to wood, cement, plaster, brick, etc.
- ▶ Nail heads are recessed for minimum exposure
- ▶ Smooth saddle prevents damage to insulation
- ▶ High-grade injection-molded polyethylene
- ▶ Resists rot, rust and the effects of temperature extremes

Dimensions = Inches

Cat No.	Fig	Used For Wire Sizes	Color	W x Ht x Inside Ht	Inner Bag	Master Bag
35000	1	2 Nail 12/2 & 14/2 Romex & UF (1/2" wide)	White	.49 x .31 x .21	100	1000
35001	1	2 Nail 10/2 Romex & UF (3/4" wide)	White	.74 x .31 x .21	100	1000
35002	2	12/2 & 14/2 Romex & UF	White	.39 x .39 x .26	100	1000
35004	3	14/3 Romex	Gray	.31 x .51 x .32	100	1000
35006	3	10/3 & 12/3 Romex	Gray	.43 x .65 x .48	100	1000
35008	3	RG 59 Coax Cable, CAT 5 UTP 4 Pair	Gray	.24 x .35 x .26	100	1000
35040	3	RG 59 Coax Cable, CAT 5 UTP 4 Pair	White	.24 x .38 x .25	100	1000
35041	3	RG 59 Coax Cable, CAT 5 UTP 4 Pair	Black	.24 x .38 x .25	100	1000
35010	3	RG 6 Coax Cable	Gray	.28 x .43 x .30	100	1000
35042	3	RG 6 Coax Cable	White	.28 x .43 x .30	100	1000
35043	3	RG 6 Coax Cable	Black	.28 x .43 x .30	100	1000
35012	3	4 Conductor Telephone Wire	Gray	.14 x .23 x .15	100	1000
35044	3	4 Conductor Telephone Wire	White	.14 x .23 x .15	100	1000
35045	3	4 Conductor Telephone Wire	Black	.14 x .23 x .15	100	1000
35014	2	Small cords such as lamp, thermostat, speaker & phone	White	.24 x .25 x .15	100	1000

## Plastic Stacking Staples



- ▶ Plastic insulated staples quickly and easily secure vertical stacks of non-metallic cable
- ▶ Electro-zinc plated nails provide strength and durability
- ▶ Smooth saddles prevent damage to insulation
- ▶ UV-protected Polyethylene saddle resists rot, rust and deterioration
- ▶ 1/2" wide, white color

Cat. No.	Cable Size	Inner Bag	Outer Bag
35016	(2) 14/2 & 12/2	50	500
35018	(3) 14/2 & 12/2	50	500
35020	(4) 14/2 & 12/2	50	500

## Plastic Service Entrance Cable Straps



- ▶ Plastic insulated straps quickly and easily secure service entrance cable
- ▶ Electro-zinc plated nails provide strength and durability
- ▶ Stabilized against UV rays and extreme cold; withstand deterioration and breakage
- ▶ Smooth saddles prevent damage to insulation
- ▶ Polyethylene Material

Cat. No.	Cable Size	Inner Bag	Outer Bag
35022	#6 & #8 SEU	50	500
35024	#2 SEU	25	250
35026	4/0 SEU	25	250
35028	#6 SER & 1/2" EMT	50	500
35030	#2 SER & 3/4" EMT	25	250
35032	2/0 SER	25	250
35034	4/0 SER	25	250