

Twisted Polypropylene Pull Rope



- ▶ Low-Friction 3-Strand Twisted Polypropylene Rope
- ▶ Slides Easily through Conduit
- ▶ Non-Sliver Surface can be handled without gloves
- ▶ Waterproof - Will not rot or mildew
- ▶ Rugged Lightweight Construction, Floats
- ▶ UV Resistant

Cat. No.	Diameter (Inches)	Length (feet)	Tensile Strength	Pulling Eye	Qty
31910	1/4"	300Ft	1125	No	1
31912	1/4"	600Ft	1125	No	1
31914	1/4"	1200Ft	1125	No	1
31916	3/8"	300Ft	2430	Yes	1
31918	3/8"	600Ft	2430	Yes	1
31920	3/8"	1200Ft	2430	Yes	1
31922	1/2"	300Ft	3780	Yes	1
31924	1/2"	600Ft	3780	Yes	1
31926	1/2"	1200Ft	3780	Yes	1

Cable Pulling Grips - Rotating Eye - Heavy Duty



- ▶ Heavy Duty Loads
- ▶ Rotating Eye
- ▶ Double Weave
- ▶ Galvanized Steel Wire Mesh
- ▶ Aluminum Alloy Pulling Eye

Cat. No.	Cable Range	Length	Max Load Lbs	Bag Qty	Box Qty
31810	.50" - .59"	21"	4000	1	20
31811	.63" - .71"	21"	4750	1	20
31812	.74" - .98"	40"	4750	1	20
31813	1.02" - 1.22"	40"	9000	1	15
31814	1.50" - 1.92"	41"	11500	1	10
31815	1.96" - 2.48"	43"	19000	1	10
31816	2.52" - 2.95"	46"	23000	1	5
31817	3" - 3.46"	49"	29000	1	5
31818	3.50" - 3.97"	51"	34000	1	3
31819	4" - 4.48"	51"	35000	1	3
31820	4.53" - 4.90"	70"	36000	1	3
31821	5.04" - 5.98"	70"	37500	1	2

Q2

Cable Pulling Grips - Flexible Eye - Medium Duty



- ▶ Medium Duty Loads
- ▶ Galvanized Steel
- ▶ Flexible Eye
- ▶ Double Weave

Cat. No.	Cable Range	Length	Max Load lbs	Bag Qty	Box Qty
31823	.51" - .59"	29"	3150	1	50
31824	.63" - .71"	32"	3900	1	50
31825	.74" - .98"	33"	4750	1	50
31826	1.02" - 1.22"	33"	6700	1	30
31827	1.50" - 1.92"	35"	11500	1	10
31828	1.96" - 2.48"	36"	13000	1	30
31829	2.52" - 2.95"	38"	17000	1	5
31830	3" - 3.46"	42"	17000	1	5
31831	3.50" - 3.97"	44"	21750	1	5

Cat. No.	Cable Range	Length	Max Load lbs	Bag Qty	Box Qty
31836	.74" - .98"	45"	4750	1	50
31837	1.02" - 1.22"	45"	6700	1	30
31838	1.50" - 1.92"	47"	11500	1	30
31839	1.96" - 2.48"	48"	13000	1	20
31840	2.52" - 2.95"	48"	17000	1	10
31841	3" - 3.46"	50"	17000	1	5
31842	3.50" - 3.97"	54"	21700	1	5