

Pulling Lubricant - Wax Based



- ▶ Superior Lubricity
- ▶ Creamy Texture applies easily and uniformly
- ▶ Clings to Cable throughout Long Pulls
- ▶ Will Not Separate after Freezing
- ▶ 30°F to 180°F (-4°C to 82°C)
- ▶ Safe, Non-Toxic, Non-Flammable and Non-Corrosive
- ▶ Easy Clean-up
- ▶ Suitable for Rubber (R, RH); Neoprene, Nylon, PVC Jackets (T, TW, THW, THHN); HDPE & XLP
- ▶ Not Recommended for use on Asbestos or Low Density Polyethylene insulated cable

Cat. No.	Size	Case Qty
99920	Quart	12
99922	Gallon	4
99924	5 Gallon	1

Pulling Lubricant - Gel



- ▶ Exceptional Lubricity for Long & High-Temperature Cable Pulls
- ▶ Compatible with all Cable types - Electrical, Fiber Optic & Datacomm
- ▶ Non-Hazardous & Non-Flammableon-Corrosive
- ▶ Apply by Hand, Brush or Pump
- ▶ Environmentally Safe - not derived from petroleum
- ▶ No gloves or eye protection needed
- ▶ Releases No Harmful Fumes or Gases
- ▶ Non-toxic, Non-staining, Hypoallergenic
- ▶ Reconstitutes with Water - Will Not Solidify in Conduit
- ▶ Cleans up Fast with water - Clear & Odorless
- ▶ Does not Stain Clothes

- ▶ Meets IEEE - 1210-1996 & ASTM D1693 Standards
- ▶ Coefficient of Friction: <23
- ▶ PH: 6-8
- ▶ Percent Solids: <3%
- ▶ Application Temperature: 30°F to 120°F (-4°C to 49°C)

Cat. No.	Size	Case Qty
99930	Quart	12
99932	Gallon	4
99934	5 Gallon	1

Pulling Lubricant - Cold Weather Gel



- ▶ Exceptional Lubricity for Long, & Low Temperature Cable Pulls
- ▶ Low Temperature: -25° F Rating
- ▶ Compatible with all Cable types - Electrical, Fiber optic & Datacomm
- ▶ Non-Corrosive, Non-Hazardous & Non-Flammable
- ▶ Apply by Hand, Brush or Pump
- ▶ Environmentally Safe - not derived from petroleum
- ▶ No gloves or eye protection needed
- ▶ Releases No Harmful Fumes or Gases
- ▶ Non-toxic, Non-staining, Hypoallergenic
- ▶ Reconstitutes with Water - Will Not Solidify in Conduit
- ▶ Cleans up Fast with water - Clear & Odorless
- ▶ Does not Stain Clothes

- ▶ Meets IEEE - 1210-1996 & ASTM D1693 Standards
- ▶ Coefficient of Friction: <23
- ▶ PH: 6-8
- ▶ Percent Solids: <3%
- ▶ Application Temperature: -25°F to 120°F (-32°C to 49°C)

Cat. No.	Size	Case Qty
99940	Quart	12
99942	Gallon	4
99944	5 Gallon	1