

Wall Mount Occupancy/Vacancy Sensor - PIR



- ▶ The Passive Infrared (PIR) Sensor detects motion by sensing the difference between body heat and ambient room temperature
- ▶ PIR Occupancy Sensor works best in offices, conference rooms and other commonly used areas without obstructions
- ▶ Vacancy Setting allows for Manual ON/Auto OFF Function
- ▶ Auto ON/OFF & Manual ON/Auto OFF
- ▶ 30Ft Range When Mounted 4Ft Height
- ▶ LED Indicator for visibility in darkened rooms
- ▶ Adjustable Light Level Sensitivity Settings
- ▶ Time Delay Off setting is adjustable from 5 Seconds to 30 minutes
- ▶ Removable Cover with mode settings and dip switch adjustments
- ▶ Decorator Wall Plate Included
- ▶ Polycarbonate
- ▶ Compatible with Incandescent, Electronic Ballast Fluorescent, Compact Fluorescent, Magnetic Low Voltage, Electronic Low Voltage, LED lighting
- ▶ Conforms to California Title 24 Energy Code
- ▶ 60Hz
- ▶ **Neutral Required**

Cat. No.	Color	Switch Type	Switch Rating	Incandescent/Fluorescent Rating	Coverage	Voltage	Time Delay	Case Qty
80520	Ivory	Auto On/Off Manual On/Auto Off	Single Pole	800W @ 120V 1200W @ 277V	180°	120-277	5 Sec-30 Min	50
80521	White	Auto On/Off Manual On/Auto Off	Single Pole	800W @ 120V 1200W @ 277V	180°	120-277	5 Sec-30 Min	50
80540	White	Auto On/Off Manual On/Auto Off	Double Pole 3-Way	800W @ 120V 1200W @ 277V	180°	120-277	5 Sec-30 Min	50

Wall Mount Occupancy/Vacancy Sensor - No Neutral - PIR



- ▶ The Passive Infrared (PIR) Sensor detects motion by sensing the difference between body heat and ambient room temperature
- ▶ Wall switch works best in offices, conference rooms and other commonly used areas
- ▶ Vacancy Setting allows for Manual ON/Auto OFF Function
- ▶ Auto ON/OFF & Manual ON/Auto OFF
- ▶ 30Ft Range When Mounted 4Ft Height
- ▶ LED indicator for visibility in darkened rooms
- ▶ Adjustable Light Level Sensitivity Settings
- ▶ Time delay Off setting is adjustable from 5 Seconds to 30 minutes
- ▶ Removable Cover with mode settings and dip switch adjustments
- ▶ Decorator Wall Plate Included
- ▶ Polycarbonate
- ▶ Compatible with Incandescent, Electronic Ballast Fluorescent, Compact Fluorescent, Magnetic Low Voltage, Electronic Low Voltage, LED lighting
- ▶ Conforms to California Title 24 Energy Code
- ▶ 60Hz
- ▶ **No Neutral Required**

Cat. No.	Color	Switch Type	Switch Configuration	Incandescent/Fluorescent Rating	Coverage	Voltage	Time Delay	Case Qty
80528	White	Auto On/Off Manual On/Auto Off	Single Pole	800W @ 120V 1200W @ 277V	180°	120-277	5 Sec - 30 Min	50
80532	White	On/Off Auto Manual On/Auto Off	Double Pole 3 Way	800W @ 120V 1200W @ 277V	180°	120-277	5 Sec - 30Min	50