

10 Outlet Surge Strip with 2 Transformers



With Phone & CATV Protection



Ultimate Protection

- ▶ Mounting key holes on back for easy hanging

- ▶ 2 Adapter Spacing for more flexibility in plug/adaptor configurations
- ▶ Slide Safety Covers for all outlets
- ▶ Lighted on/off Circuit Breaker Switch
- ▶ LED indicator light for function status
- ▶ Sliding Cable Organizer Bracket
- ▶ SJT 14/3, 15A 120V 60Hz
- ▶ Surge Dissipation: 3600 Joules
- ▶ Clamping Voltage: 400V L-N, N-G, L-G
- ▶ Max Surge Voltage: 6,000V
- ▶ Max Current Spike: 135,000A
- ▶ EMI/RFI Filtering,
- ▶ 3-Line Surge Protection
- ▶ Power Shutdown Feature
- ▶ MCOV 127 Vac. In 3KA
- ▶ UL 1449

Cat. No.	Joules	Cord Length	Box Qty
89093	3600	6Ft	8

Heavy Duty Metal Power Bar Surge Strip



- ▶ Mounting key holes on back for easy hanging

- ▶ 12 Outlet 48" long power surge strip
- ▶ Durable construction for Lab, Work-Shop & Office Applications etc.
- ▶ Brushed Aluminum Housing
- ▶ Lighted On/Off Circuit Breaker Switch
- ▶ LED indicator light for function status
- ▶ 15A 120V, 1875W 60Hz
- ▶ Surge Dissipation: 450 Joules
- ▶ Clamping Voltage: 500V L-N, N-G, L-G
- ▶ Max Surge Voltage: 6000V
- ▶ Max Current Spike: 22500A
- ▶ 6Ft SJT 14/3 Power Cord
- ▶ EMI/RFI Filtering
- ▶ 3-Line Surge Protection
- ▶ UL 1449

Cat. No.	Joules	Cord Length	Box Qty
89100	450	6 Ft	4

Whole-House Lightning Arrester/Surge Suppressor



- ▶ Installs at electrical panel, electrical disconnect to protect Pumps, Motors, HVAC Condensers & Incoming Utility Power for Residential & Light Commercial Applications
- ▶ Hardwire Parallel Connection
- ▶ Unlimited (Parallel Installation) Continuous Current
- ▶ Response Time: <1 nSec component level
- ▶ Automatic Reset to Protect against Multiple Surge Events
- ▶ MCOV: 130 VAC (L - G), 260 VAC (L - L)
- ▶ AC protection Modes: 500V (L - G) & 900V (L - L)
- ▶ Short Circuit Current Rating: 10,000A
- ▶ Operating Frequency: 0 - 400 Hz
- ▶ Protection Type: SPD Type 2
- ▶ Service Voltage: 120/240VAC (2w+G) Single Phase
- ▶ WeatherProof High Impact ABS Non-Metallic Housing
- ▶ Housing size: 3" x 2.25" x .75"
- ▶ Indicator light for surge protection, grounding and power status
- ▶ cULus Listed, UL 1449, 3rd Edition; ANSI/IEEE C62.11

Cat. No.	Indicator Light	Surge Current	Max Energy Dissipation	Case Qty
89114	Yes	72,000 A.	940 Joules	48