



Catalog Number 12088
UPC Number 60198612088
Description Nylon Insulated Female Receptacle
Bullet Disconnect
12-10 AWG .193 OD



Features


- Nylon Color Coded insulation for easy identification
- Manufactured from high strength copper alloy
- Electro-tin plated for corrosion resistance
- Expanded insulation eliminates strand “Hang Up”, provides strain relief & excellent UV, temperature and chemical resistance
- Wire range stamped on the surface for easy interpretation
- Brazed seams prevent splitting under maximum pressure
- Serrated barrel & extended copper crimp sleeve provides excellent electrical contact & pull-out force resistance

General

Insulation Type Nylon
Material Brass/Copper
Finish Electro-Tin Plated
Color Yellow
Wire Range 12-10
Bullet Size 0.197

Dimension Information

T Inches (mm) 0.018
L Inches (mm) 0.965
B Inches (mm) 0.512
C Inches (mm) 0.134
D Inches (mm) 0.256
F Inches (mm) 0.276
W Inches (mm) 0.193



Specifications

Temperature Rating 105°C
Voltage Rating 600 V
Flammability Rating UL94V-O
Amp Rating 12 AWG 20 Amps
10 AWG 24 Amps

Packaging

Bag Qty 100
Master Bag Qty 1000

Certifications

UL Yes
cUL Yes
RoHS Yes

Morris Products 53 Carey Road, Queensbury, NY 12804

www.morrisproducts.com

