


10" 30W COMMERCIAL DOWNLIGHT












Part#	Housing Color	Wattage	Lumens	ССТ	Voltage	Input Current @ 120V	Lumens/ Watt	Energy Star
72666	White	30W	2900	4000K	120-277	.2454A	96	Yes





10" 30W **COMMERCIAL DOWNLIGHT**

Construction:

Technical Specifications:

Operating Temperature: Electrical:

Minimum Starting -31° - 122° F Input Voltage: 120 thru 277

Current: .2454A @ 120V

Power Factor: ≥.9 Housing: Aluminum Housing

White Trim

Product Parameters: IP Rating: IP43 Wet Indoor Location Rated

30 Watts

Frequency: 60Hz

Efficacy: 96 lumens per watt Lens Material: Frosted Polycarbonate Lens

50,000+ LED Life Span

CCT: 4000k (Neutral White) Mounting: Ceiling Mount

Chromacity Measurements:

Beam Angle: 35° Listings: UL, Energy Star

BUG Rating: N/A

CRI: ≥ 82.2 R9: 8

Carton Qty: 1 DUV: 0.00034 Weight: 7 lb

Chromaticity (x,y): x=.4638; y=.4123

Chromaticity (u,v): u=.2642; v= .3524 Warranty: Morris Products carries a 5 year warranty from date of purchase

against defects in materials and workmanship (assuming normal

and proper usage).

Component Specifications:

LED: SSC3030

Driver: 120-277V 50-60HZ

Driver Output Volts: Driver Output Amps:

Surge Protection: 2500V

Dimming: 0-10 Dimming