

72667 - 10" COMMERCIAL RECESSED DOWNLIGHT








30W 5000K 120-277V






FEATURES:

- Ideal for retrofit applications
- Aluminum housing/trim paintable
- 0-10V dimming
- 50,000 + hour LED life expectancy
- 5 Year Warranty

- IP43 Damp Location Rated
- ETL Listed, Energy Star Listed
- Order Qty of 1 = 1 Piece
- Contains a 15" Greenfield wire whip to driver and line side with box connectors included for easy install

Part#	Housing Color	Wattage	Lumens	ССТ	Voltage	Input Current @ 120V	Lumens/ Watt	Energy Star
72667	White	30W	2850	5000K	120-277	.2454A	96	Yes

PHOTOMETRY





72667 - 10" COMMERCIAL RECESSED DOWNLIGHT

30W 5000K 120-277V

Technical Specifications:

Electrical:

Input Voltage: 120 - 277 Current: .2454A @ 120V

Frequency: 60Hz Power Factor: ≥.9

Product Parameters:

30 Watts

Efficacy: 96 lumens per watt

50,000+ LED Life Span CCT: 5000K (Cool White)

Chromacity Measurements:

Beam Angle: 35° BUG Rating: N/A

CRI: ≥ 82.2 R9: 8

DUV: 0.00034

Chromaticity (x,y): x=.4638; y= .4123 Chromaticity (u,v): u=.2642; v= .3524

Component Specifications:

LED: SSC3030

Driver: 120-277V 50-60HZ Surge Protection: 2500KV

Dimming: 0-10V Dimming

Operating Temperature:

Minimum Starting -31° - 122° F

Construction:

Housing: Aluminum Housing

White Trim

IP Rating: IP43 Wet Indoor Location Rated

Lens Material: Frosted Polycarbonate Lens

Mounting: Ceiling Mount

Listings: ETL, Energy Star

Carton Qty: 1 Weight: 1 lb

Warranty:

Morris Products carries a 5 year warranty from date of purchase against defects in materials and workmanship (assuming normal

and proper usage).