

72740B - 6" SURFACE MOUNT DISK LIGHT










COLOR SELECTABLE, PIR SENSOR 15W





FEATURES:

- 5 Color Selectable: 2700K/3000K/3500K/4000K/5000K
- High quality iron shell with frosted PC diffuser
- Low profile, no flicker
- With multiple apertures, can be installed into any 5 or 6 inch recessed can, or any 4 inch junction box
- Built with the highest quality 120V drivers, ensuring energy efficiency

- cETLus Listed, Energy Star Listed
- PIR Sensor included
- Wet-location rated, ideal for garage, corridor hallways warehouse, in walk in closet, utility rooms and attics
- 50,000+ hours LED Life expectancy
- Compatible with most triac dimmers
- Suitable for closet installations when installed within NEC requirements
- Title 24/JA8 Compliant for High Efficacy LED Lighting in California

Part#	Housing Color	Wattage	Lumens	ССТ	Voltage	CRI	Lumens/ Watt	Energy Star
72740B	White	15W	1126	2700/3000/ 3500/4000/ 5000K	120V	<u>></u> 90	75	Yes



72740B - 6" SURFACE MOUNT DISK LIGHT

COLOR SELECTABLE PIR SENSOR 15W

PIR SENSOR

Anticlockwise to open the outside lens



The delay auto turn off light has the option of 1 minute /5 minutes /8 minutes.




Product view



PIR SENSOR ON/OFF FUNCTION

During the day or evening, when the PIR sensor detects someone entering the sensing range, the light will turn on automatically; When the person leaves the sensing range, it will automatically turn off the lights after a few minutes (you can mobilize the switch on the side of the light to select the delay time at 1min/5min/8min).


The detection range of PIR sensor is 16 feet;



When the person is in the sensing area, the light will stay on until the person leaves;



When the person leaves the sensing range, it will automatically turn off the lights after a few minutes.





72740B - 6" SURFACE MOUNT DISK LIGHT

COLOR SELECTABLE, PIR SENSOR 15W

TECHNICAL SPECIFICATIONS:

VOLTAGE: 120V

POWER FREQUENCY: 60 Hz

POWER FACTOR: > 0.9

5 CCT: 2700K/3000K/3500K/4000K/5000K

CRI: 90

BEAM ANGLE: 120 Degrees

LAMP BEAD TYPE: 2835

CONTROL METHOD: PIR Sensor

DELAY TURNING OFF LIGHT: 1 min/5 min/8 min

LIFESPAN: >50,000 Hours

OPERATING TEMP: Minimum Starting -4° - 122° F

DIMMABLE: Compatible with most triac dimmers

to give user a smooth 100%-5% dimming to

choose the desired brightness.

RATING: Suitable for wet locations - IP43

WARRANTY: 5 years

CONSTRUCTION:

HOUSING: High Quality Iron Shell with Frosted PC Diffuser,

White finish

LENS MATERIAL: Adjustable Frosted Polycarbonate Lens

MOUNTING: Surface Mounting

LISTINGS: cETLus, Energy Star, Title 24/JA8 Compliant

CARTON QTY: 24

N.W.: 7.2 KGS

G.W.: 8.6 KGS

CBM: 0.037

WARRANTY:

Morris Products carries a 5 year warranty from date of purchase against defects in materials and workmanship (assuming normal and proper usage).