


## 73524 - ROUND HEAD EMERGENCY LIGHT



WHITE, HIGH OUTPUT, REMOTE CAPABLE, WITH SELF DIAGNOSTIC





## **FEATURES:**

- Self Diagnostic Test Feature continuously diagnoses units performance and tests system to ensure reliable operation and to meet electrical & Life Safety Codes
- · Completely Self-Contained
- · Fully Automatic Operation
- · Compact, Low Profile Designs in Neutral Finish
- · Push to Test Switch
- · 3.6 Volt Maintenance Free Ni-Cad Battery
- · Environmental Coated, Solid State Charger
- $\cdot\,$  2 x 12 LED 76 Lumen Fully Adjustable Glare Free Lamps
- · Automatic, Low Voltage Disconnect (LVD)
- · Universal Transformer for 120 or 277 VAC

- Universal J-Box Mounting Plate
- Injection Molded, V-O Flame Retardant, High Impact, Thermoplastic Housing
- Charge Rate/Power on LED Indicator Light
- 90 Minute Emergency Operation
- Damp Location Rated
- Remote Capable
  - o 4 Lamps 90 Minute Battery Run Time
  - o 3 Lamps 120 Minute Battery Run Time
  - o 2 Lamps 180 Minute Battery Run Time
- Self Diagnostic Features:
  - On-Line real time monitoring of battery charging, disconnection or failure and local or remote lamp failure
  - Self Testing and 15 Minute discharge every 30 days
  - Self Testing and 90 Minute discharge annually

Part#	Туре	Volts	Lumens per head	Housing Color	Battery
73524	Remote, Self Diagnostic	120/277	76	White	Ni-Cad

## 73524 Remote, Self Diagnostic 120/277 76 White Ni-Ca

Dimension information					
L Inches (mm)	9	Packaging			
H Inches (mm) 4.00		Box Qty	1		
Depth Inches (mm)	2.75	Master Carton Qty Certifications	12		
		UL	UL 924		
Specifications		cUL	No		
Input Rating Amps:	1.03	RoHS	Yes		
Input Rating Watts:	.85 @ 120V .80 @ 277V				
Lamp Type: Voltage	LED 76 Lumens Per Head				

Rating: Flammability 120/277 Rating: Battery UL94V-0

Operation: 3.6 Volt Nickel Cadmium - 90 Minutes Min