

# **74002C -** LED AREA LIGHT SHOEBOX GEN 4

120-277V 100W 5000K















60-100W



Yoke Sold Separately

#### **FEATURES:**

- SMD 3030 LEDs
- Corrosion resistant Die Cast Aluminum housing
- Polycarbonate Optic Lens
- Superior Architectural Powder Coat Finish
- Stainless Steel Hardware

- Photo Control must be Purchased Separately
- Light Pattern: Type III
- IP65 (NEMA 4X) Dust & Water Tight
- cULus Listed for Wet Locations
- DLC PRODUCT ID#: PSBD7P92
- 5 Year Warranty


| Part#  | Housing<br>Color | Wattage | Lumens | сст   | Voltage  | Beam<br>Angle | Lumens/<br>Watt | DLC<br>PRODUCT<br>ID#: |
|--------|------------------|---------|--------|-------|----------|---------------|-----------------|------------------------|
| 74002C | Bronze           | 100W    | 13,800 | 5000K | 120-277V | 134°          | 138lm/w         | PSBD7P92               |





## 74002C - LED AREA LIGHT SHOEBOX GEN 4


120-277V 100W 5000K

#### **PHOTOMETRY:**











## 74002C - LED AREA LIGHT SHOEBOX GEN 4

120-277V 100W 5000K

**TECHNICAL SPECIFICATIONS:** 

**Electrical:** 

Input Voltage: 120-277V Current: .32A

@ 277V Frequency: 60Hz

Power Factor: ≥.0.9 THD: 12.3% @ 277V

**Product Parameters:** 

100 Watts

Efficacy: 138 lumens per watt 50,000+

LED Life Span CCT: 5000K

**Chromacity Measurements:** 

Beam Angle: 134°

CRI: 72 R9: -33

DUV: 0.00001

Chromaticity (x,y): x=0.4373; y=0.4035Chromaticity (u,v): u=0.2511; v=0.5212

**Component Specifications:** 

LED: SMD3030

Driver Voltage: 347-480V Frequency: 50-60HZ

Dimming: 0-10V

\*Photo Control:

Twist lock receptacle and shorting included.

Photocell sold separately.

LED Twist-Lock Style Photocells: 39106 (120-277V)

LED Twist-Lock Style Photocells: **39107** (480V)

\*Twist lock receptacle is installed on fixture and

shorting cap is include in the box

**Operating Temperature:** 

Minimum Starting: -22°F To 122°F

**Construction:** 

Housing: Corrosion resistant Die Cast Aluminum housing

IP Rating: IP65 Wet Location Rated

Lens Material: Polycarbonate

EPA: 1.15 ft<sup>2</sup>

Weight: 9.5lbs

Mounting Accessories Sold Separately

Listing: cULus

DLC PRODUCT ID#: PSBD7P92

**Accessories (Sold Separately):** 

Pole Arm Mount (80-300W) Bronze - For Round and Square Poles -

CAT#: 74032A

• Slipfitter Mount (80-300W) Bronze - CAT#: 74034A

• Trunnion Mount (80-300W) Bronze - CAT#: 74038C

Universal Mount (80-300W) Bronze - CAT#: 74043A

Yoke Mount (60-100W) Bronze - CAT#: 74733C

Microwave Motion Sensor (120-277V and 480V Only) - CAT#:

74072C

• Microwave Motion Sensor Remote (Optional, for use with 74072C)

-CAT#: 74188B

Warranty:

Morris Products carries a 5 year warranty from date of purchase against defects in materials and workmanship (assuming normal

and proper usage).