





74027C - LED AREA LIGHT SHOEBOX GEN 4


120-277V 300W 5000K



Adapter Included with fixture



Trunnion Sold Separately



Yoke Sold Separately

240-300W

Twist Lock Receptacle & Shorting Cap Included
Photocell Sold Separately - Cat# 39106

FEATURES:

- SMD 3030 LEDs
- Corrosion resistant Die Cast Aluminum housing
- Polycarbonate Optic Lens
- Superior Architectural Powder Coat Finish
- Stainless Steel Hardware
- Photo Control must be Purchased Separately
- Light Pattern: **Type IV**
- IP65 (NEMA 4X) Dust & Water Tight
- cULus Listed for Wet Locations
- DLC PRODUCT ID#: P552R3XV
- 5 Year Warranty



Part#	Housing Color	Wattage	Lumens	CCT	Voltage	Beam Angle	Lumens/Watt	DLC PRODUCT ID#:
74027C	Bronze	300W	43,060	5000K	120-277V	121°	143lm/w	P552R3XV



74027C - LED AREA LIGHT SHOEBOX GEN 4

120-277V 300W 5000K


PHOTOMETRY:



Illuminance at a Distance

	Center Beam fc	Beam Width	
17.0ft	24.1 fc	41.3 ft	60.0 ft
34.0ft	6.03 fc	82.7 ft	120.1 ft
51.0ft	2.68 fc	124.0 ft	180.1 ft
68.0ft	1.51 fc	165.3 ft	240.1 ft
85.0ft	0.97 fc	206.7 ft	300.2 ft
102.0ft	0.67 fc	248.0 ft	360.2 ft

- Vert. Spread: 101.1°
- Horiz. Spread: 121.0°





74027C - LED AREA LIGHT SHOEBOX GEN 4

120-277V 300W 5000K

Technical Specifications:

Electrical:

Input Voltage: 120-277V

Current: 1.13A @ 277V

Frequency: 60Hz

Power Factor: ≥ 0.9

THD: 9.1% @ 277V

Product Parameters:

300 Watts

Efficacy: 143 lumens per watt

50,000+ LED Life Span

CCT: 5000K

Chromacity Measurements:

Beam Angle: 121°

CRI: 72

R9: -33

DUV: -0.0004

Chromaticity (x,y): x=0.4364; y= 0.4028

Chromaticity (u,v): u=0.2508; v= 0.5208

Component Specifications:

LED: SMD3030

Driver Voltage: 120-277V

Frequency: 50-60HZ

Dimming: 0-10V

*Photo Control:

Twist lock receptacle and shorting included.

Photocell sold separately.

LED Twist-Lock Style Photocells: **39106** (120-277V)

LED Twist-Lock Style Photocells: **39107** (480V)

*Twist lock receptacle is installed on fixture and shorting cap is include in the box

Operating Temperature:

Minimum Starting: -22°F To 122°F

Construction:

Housing: Corrosion resistant Die Cast Aluminum housing

IP Rating: IP65 Wet Location Rated

Lens Material: Polycarbonate

EPA: 2.51 ft²

Weight: 16.3lbs

Mounting Accessories Sold Separately

Listing: cULus

DLC PRODUCT ID#: P552R3XV

Accessories (Sold Separately):

- Pole Arm Mount (80-300W) Bronze - For Round and Square Poles - CAT#: 74032A
- Slipfitter Mount (80-300W) Bronze - CAT#: 74034A
- Trunnion Mount (80-300W) Bronze - CAT#: 74038C
- Universal Mount (80-300W) Bronze - CAT#: 74043A
- Yoke Mount (240-300W) Bronze - CAT#: 74737C
- Microwave Motion Sensor (**120-277V and 480V Only**) - CAT#: 74072C
- Microwave Motion Sensor Remote (Optional, for use with 74072C) -CAT#: 74188B

Warranty:

Morris Products carries a 5 year warranty from date of purchase against defects in materials and workmanship (assuming normal and proper usage).