


MORRIS CAT#: 75124A LED Gooseneck Flood light 40W, 120/240/277V, 5000K, Black















Features:

- Clear Polycarbonate Lens
- Swivel head fixture
- Operating Temperature: -40°F to 122°F
- Photocell Included

- Powder Coated: Black
- Aluminum Housing
- Environment: IP65 Rated -Suitable for Wet Locations
- Certification: ETL
- DLC PRODUCT ID#: S-QPWV02
- 5 Year Limited Warranty

Part#	Input/ Wattage	Volts	Lumens	ССТ	CRI	Dimming	Light Pattern	Lumens/ Watt	DLC PRODUCT ID#:
75124A	40W	120/240/277	4,800	5000K	>70	N/A	Outdoor	120lm/w	S-QPWV02

PHOTOMETRY





MORRIS CAT#: 75124A LED Gooseneck Flood light 40W, 120/240/277V, 5000K, Black

Technical Specifications:

Electrical:

Input Voltage: 120V/240V/277V

Current: .33A@120V Frequency: 50/60Hz Power Factor: ≥.99 THD: 15% @120V

Product Parameters:

Input Watts: 40W

Lumens: 4,800

Efficacy: 120 lumens per watt 50,000+ Hour L70 Life Span CCT: 5000K (Cool White)

Chromacity

Measurements:

Beam Angle: Outdoor

CRI: >70 R9: 0

Operating Temperature:

Minimum Starting: -40°F to 122°F

Construction:

Housing: Aluminum Housing

Powder Coat Finish: Black

IP Rating: IP65 - Suitable for wet locations

Lens Material:Clear Polycarbonate Lens

Mounting: Wall

Listings:

ETL

DLC PRODUCT ID#: S-QPWV02

Component

Specifications:

LED: LumiLED LUXEON 3030 Driver Voltage: 120/240/277V

Frequency: 50-60Hz

Dimming: N/A

Warranty:

Morris Products carries a 5 year warranty from date of purchase against defects in materials and workmanship (assuming normal

and proper usage).