






77009A - GEN 2 SPORTS LIGHT

20° BEAM ANGLE

277-480V 750W 5000K



FEATURES:

- 360° Lighting
- 20° Beam Angle
- Big Heat Sink with Excellent Heat Dissipation
- Internal Driver - Long Life High Efficiency LEDs
- Advanced Multi-faceted Optics
- SOSEN Drivers/SMD3030 LEDs
- 5' Whip Length
- 240° Tilt; 220° Rotation
- Direct Replacement for Metal Halide
- 10KV Surge Suppression
- IP65 Waterproof Rating
- Lightweight - 33 lbs
- -40° To 113° Operating Temperature
- 5 Year Warranty

Part#	Wattage	Voltage	Lumens	CCT	CRI	Dimming	Light Pattern	Lumens/Watt
77009A	750W	277-480V	94824	5000K	>70	0-10V	20°	126




77009A - GEN 2 SPORTS LIGHT 20° BEAM ANGLE


277-480V 750W 5000K

PHOTOMETRY:

Luminous Intensity Distribution Curve



The Average Illuminance Effective Figure





77009A - GEN 2 SPORTS LIGHT 20° BEAM ANGLE

277-480V 750W 5000K

TECHNICAL SPECIFICATIONS:

Electrical:

Input Voltage: 277-480V

Current: 1.60 @ 480V

Frequency: 60Hz

Power Factor: ≥ 0.99

THD: $>20\%$

Product Parameters:

750 Watts

Lumens: 94,824

Efficacy: 126 Lumens Per Watt

50,000+ Hour LED Life Span

CCT: 5000K (Cool White)

Chromaticity Measurements:

Beam Angle: 20°

BUG Rating: B5-U0-G2

CRI: >70

R9: -29

DUV: -0.0003

Chromaticity (x,y): $x=.3874$; $y=.3818$

Chromaticity (u,v): $u=.2294$; $v=.5144$

Component Specifications: LED:

SMD3030

Driver: 277-480V 50-60HZ

Driver Output Volts: 96VDC Driver

Output Amps: 7A

10,000V Surge Protection

Dimming: 0-10V

Operating Temperature:

Minimum Starting -40°F - 113°F

Construction:

Housing: Aluminum

Powder Coated

5' Whip Length

IP Rating: IP65

Lens Material: Polycarbonate

Mounting: Yoke (Bracket) OR Slipfitter

Listings: cULus

Carton Qty: 1

Weight: 72 lbs

Warranty:

Morris Products carries a 5 year warranty from date of purchase against defects in materials and workmanship (assuming normal and proper usage).