



Catalog Number See Table
UPC Number
Description Bi-Metallic Pin Terminals
Solid Copper Pin
Offset

Features

- Manufactured from High Strength High Conductivity Aluminum Alloy
- Electro Tin Plated
- AL9CU Rated for Copper or Aluminum Conductors
- Oxide Inhibitor Coated Barrel
- EDPM Rubber Insulating Cover

General

Material: Aluminum Alloy
EDPM Rubber Insulating Cover
Wire Range: Conductor Size Pin Size
#6 #4
Thru 750 MCM Thru 500 MCM

Dimension Information

Length: See Table

Specifications

Temperature Rating: N/A
Voltage Rating: 600
Flammability Rating: N/A
Amp Rating: To Conductor

Packaging

Box Qty See Table

Certifications

UL Yes
cUL Yes
RoHS Yes

Cat. No.	Wire Size	Pin Size	O.D.	I.D.	Pin Dia.	Total Length	Pin Length	Body Length	Color Code	Inner Box	Outer Box
90985	2/0	1	0.85	0.44	0.33	2.69	1.12	1.57	White	10	100
90986	3/0	1/0	0.85	0.5	0.37	2.8	1.25	1.55	White	10	100
90987	4/0	2/0	0.85	0.547	0.42	2.78	1.27	1.51	White	10	100
90988	250 MCM	3/0	1.09	0.594	0.46	2.78	1.27	1.51	Brown	10	100
90989	300 MCM	4/0	1.09	0.657	0.53	3.08	1.46	1.62	Brown	10	100
90990	350 MCM	250	1.09	0.704	0.57	3.08	1.46	1.62	Brown	10	100
90991	400 MCM	300	1.31	0.763	0.62	3.38	1.68	1.7	Pink	10	100
90992	500 MCM	350	1.31	0.842	0.68	3.38	1.68	1.7	Pink	10	100
90993	600 MCM	400	1.46	0.821	0.72	3.99	1.72	2.27	Yellow	3	30
90994	750 MCM	500	1.46	1.03	0.81	4.18	1.72	2.46	Yellow	3	30

www.morrisproducts.com

Morris Products 53 Carey Road, Queensbury, NY 12804