



**MORRIS CAT#: 91802 - 91811**  
**C-Taps - Copper**



FIG 1

**Features:**

- Copper C Taps are UL 467 Listed for Direct Burial & Grounding/Bonding Applications
- Applications include Copper To Copper Splice/Tap or Stub/Pigtail Connections and Grounding
- Allows for 2 Continuous Parallel Conductors
- High Strength Electrolytic Copper
- Compact Size
- Range Taking
- 600 volt
- UL/CSA Listed

DIMENSIONS = INCHES

CAT. NO.	FIG	DIE COLOR	CONDUCTOR RANGE		STRIP L	DIMENSIONS				BOX QTY
			RUN	TAP		L	W (ID)	H	T	
91802	I	RED	14	16-14	1/2	.32	.18	.16	.07	275
			12	16-12						
			10	14						
91803	I	BLUE	10	10	5/8	.61	.32	.36	.07	275
			8	12						
91804	I	GRAY	6	10-12	5/8	.61	.32	.43	.07	200
			8	8-10						
91805	I	BROWN	4	8-10-12	1-1/4	1.17	.41	.43	.07	150
			6	6-8						
91806	I	GREEN	4	6-4	1-1/4	1.17	.45	.52	.07	100
			3	12-6						
91807	I	PINK	4	4	1-1/4	1.17	.49	.54	.07	100
			3	4-6						
			2	12-6						
91808	I	BLACK	1	12-4	2	1.75	.53	.64	.07	100
			2	4-6						
			3	4-3						
91809	I	ORANGE	1/0	12-4	2	1.75	.61	.71	.09	50
			1	4-3						
			2	4-2						
91810	I	PURPLE	2/0	12-4	2	1.75	.69	.77	.09	30
			1/0	2						
			1	1-2						
91811	I	YELLOW	3/0	2-12	1	1.75	.81	1.07	.09	30
			2/0	1-2						
			1/0	1/0-1						