



**MORRIS CAT#: 91812 - 91818**  
**C-Taps - Copper - Medium Wall**



FIG 2

**Features:**

- Medium Wall Design with Raised Separating Barrier for Larger Gauge Wire Applications
- Copper C Taps are UL 467 Listed for Direct Burial & Grounding/Bonding Applications
- Applications include Copper To Copper Splice/Tap or Stub/Pigtail Connections and Grounding
- Allows for 2 Continuous Parallel Conductors
- High Strength Electrolytic Copper
- Compact Size
- Range Taking
- 600 volt
- UL/CSA Listed

DIMENSIONS = INCHES

CAT. NO.	FIG	DIE COLOR	CONDUCTOR RANGE		STRIP L	DIMENSIONS				BOX QTY
			RUN	TAP		L	W (ID)	H	T	
91812	2	YELLOW	1/0	1/0-2	1	1.30	.79	.63	.16	50
			2/0	2/0-4						
			3/0	1/0-6						
			4/0	1-8						
			2/0	2/0-1						
91813	2	BLUE	3/0	3/0-3	1	1.46	.79	.79	.20	50
			4/0	4/0-4						
			250	1/0-8						
			2/0	2/0-1						
91814	2	BLUE	3/0	3/0-3	1-1/8	1.67	1.03	.85	.20	25
			4/0	4/0-4						
			250	3/0-6						
			300	2/0-8						
			4/0	4/0-2/0						
91815	2	BROWN	250	250-1	1-1/8	1.71	1.03	.90	.20	25
			300	4/0-4						
			350	3/0-6						
			250	250						
91816*	2	BROWN 600MCM BLACK 750MCM	300	300-3/0	1-5/16	1.87	1.28	1.02	.20	15
			350	350-1/0						
			400	300-2						
			450	250-4						
			500	250-6						
91817*	2	WHITE	350	350-4/0	1-5/16	2.17	1.29	1.18	.30	10
			400	400-2/0						
			450	450-1						
			500	500-2						
91818*	2	-	750-500	4/0-6	2-3/4	2.75	1.97	1.34	.16	5
			750	750-4/0						

\*NOT LISTED FOR DIRECT BURIAL, GROUNDING OR BONDING