



Midget Fast Acting Fuses - 600V



- Use with street lighting holders, HID lighting, control circuits, electronic equipment protection
- Compact dimensions
- Interrupting Rating: 100kA RMS Amps
- Fast-acting design responds quickly to both overloads and short-circuit current
- UL Listed, CSA Certified

CAT. NO.	DESCRIPTION	BOX QTY	MIN. ORDER QTY
T626-MCL1	1 AMP	10	10
T626-MCL1.5	1.5 AMPS	10	10
T626-MCL2	2 AMPS	10	10
T626-MCL2.5	2.5 AMPS	10	10
T626-MCL3	3 AMPS	10	10
T626-MCL5	5 AMPS	10	10
T626-MCL6	6 AMPS	10	10
T626-MCL8	8 AMPS	10	10
T626-MCL10	10 AMPS	10	10
T626-MCL12	12 AMPS	10	10
T626-MCL15	15 AMPS	10	10
T626-MCL20	20 AMPS	10	10
T626-MCL25	25 AMPS	10	10
T626-MCL30	30 AMPS	10	10

FUSES

Midget Fast Acting Fuses - 250V



- Supplemental protection for noninductive control and lighting circuits
- Interrupting Rating:
- 10kA@ 125VAC 20-30A
- 35A @ 250VAC 0.5-1A
- 100A@ 250VAC 1.5-6A
- 200A@ 250VAC 6.5-10A
- 750A@ 250VAC 12-15A
- Compact dimensions
- Economical laminated paper tube design
- UL Listed, CSA Certified

CAT. NO.	DESCRIPTION	BOX QTY	MIN. ORDER QTY
T626-MOL1	1 AMP	10	10
T626-MOL2	2 AMPS	10	10
T626-MOL5	5 AMPS	10	10
T626-MOL6	6 AMPS	10	10
T626-MOL10	10 AMPS	10	10
T626-MOL12	12 AMPS	10	10
T626-MOL15	15 AMPS	10	10
T626-MOL20	20 AMPS	10	10
T626-MOL25	25 AMPS	10	10
T626-MOL30	30 AMPS	10	10

Midget Time Delay Fuses - 500V



- Supplemental protection of transformers, solenoids, and other high inrush circuits
- Interrupting Rating: 10kA RMS Amps
- Compact dimensions
- Fiber tube construction
- Time-delay allows harmless inductive surges to pass without needless fuse opening
- UL Listed, CSA Certified

CAT. NO.	DESCRIPTION	BOX QTY	MIN. ORDER QTY
T626-MEQ.5	.5 AMP	10	10
T626-MEQ1	1 AMP	10	10
T626-MEQ2	2 AMPS	10	10
T626-MEQ3	3 AMPS	10	10
T626-MEQ4	4 AMPS	10	10
T626-MEQ5	5 AMPS	10	10
T626-MEQ6	6 AMPS	10	10
T626-MEQ8	8 AMPS	10	10
T626-MEQ10	10 AMPS	10	10
T626-MEQ12	12 AMPS	10	10
T626-MEQ15	15 AMPS	10	10
T626-MEQ20	20 AMPS	10	10
T626-MEQ25	25 AMPS	10	10
T626-MEQ30	30 AMPS	10	10

Midget Time Delay Fuses - 250V



- Supplemental protection of small motors, transformers, solenoids, and other high inrush power electronic circuits
- Compact dimensions
- Fiber tube construction
- Interrupting Rating: 10kA RMS Amps @125V
- Dual-element construction allows harmless inductive surges to pass without opening
- UL Listed, CSA Certified

CAT. NO.	DESCRIPTION	BOX QTY	MIN. ORDER QTY
T626-MEN1	1 AMP	10	10
T626-MEN1.5	1.5 AMPS	10	10
T626-MEN2	2 AMPS	10	10
T626-MEN3	3 AMPS	10	10
T626-MEN3.2	3.2 AMPS	10	10
T626-MEN4	4 AMPS	10	10
T626-MEN5	5 AMPS	10	10
T626-MEN6	6 AMPS	10	10
T626-MEN7	7 AMPS	10	10
T626-MEN8	8 AMPS	10	10
T626-MEN10	10 AMPS	10	10
T626-MEN12	12 AMPS	10	10
T626-MEN15	15 AMPS	10	10
T626-MEN20	20 AMPS	10	10
T626-MEN25	25 AMPS	10	10
T626-MEN30	30 AMPS	10	10