



- 70° Ambient Temperature
- Installs with all Standard 48 Frame Mounting Brackets
- Standard Shaft Length, Diameter, and Flats
- Drain Holes with Plugs in both end plates
- Automatic Thermal Overload Protector
- Standard 48 Frame Motor Casing Size
- Low Power Consumption
- Electrically Reversible
- Continuous Air Over
- Class B Insulation
- Quiet Operation
- Extended Studs
- 30" Leads
- 60 HZ
- cURus Listed
- Shaft Diameter 1/2"



| CAT. NO.    | HP  | VOLTAGE | SPEED  | FLA | CASE QTY |
|-------------|-----|---------|--------|-----|----------|
| TWG840739HT | 3/4 | 460     | 1075/1 | 5.3 | 1        |



## Lug Motor Mounting Bracket

| CAT. NO. | DESCRIPTION                 | MOUNT TYPE | SIZE   | UOM | CASE QTY |
|----------|-----------------------------|------------|--------|-----|----------|
| TA80293  | BOLT CIRCLE 6-7/8 TO 8-1/8" | LUG        | 5-1/2" | EA  | 50       |



## Adjustable Diameter Mounting Bracket

| CAT. NO. | PRIOR CAT. NO. | DESCRIPTION                             | MOUNT TYPE           | SIZE   | UOM | CASE QTY |
|----------|----------------|---|----------------------|--------|-----|----------|
| TFM556   | TDMB-3         | 3 LEGS PLASTIC INSERTS FOR 42 FRAME FIT | TORSION FLEX BRACKET | 5-1/2" | EA  | 50       |



## Blower Motor Mounting Bracket

| CAT. NO. | PRIOR CAT. NO. | DESCRIPTION   | MOUNT TYPE | SIZE   | UOM | CASE QTY |
|----------|----------------|---|------------|--------|-----|----------|
| TA60459  | TDMB-1         | BRACKETS, RUBBER GROMMETS, AND MOUNTING HARDWARE INCLUDED | BELLY BAND | 5-1/2" | EA  | 108      |

## Standard PTC Relay and Hard Start Capacitors

- Wired with "Piggy-Back" terminals for easy installation on run capacitors
- Designed for 115 volt thru 277 volt systems
- Mounts easily with either screw or clip
- Increases compressor starting torque for faster recycling
- For all permanent split capacitor, single phase air conditioning and heat pump systems

| CAT. NO. | PRIOR CAT. NO. | OPERATING VOLTAGE (VAC) | RECOMMENDED RANGE | INCREASE IN TORQUE % | UOM | CASE QTY |
|----------|----------------|-------------------------|-------------------|----------------------|-----|----------|
| TOS5     | TDST-5         | 115-277                 | 1/2HP TO 10HP     | 300%                 | EA  | 20       |
| TOS6     | TDST-6         | 115-277                 | 1/2HP TO 10HP     | 500%                 | EA  | 25       |
| TOS8     | -              | 115-277                 | 1/2HP TO 10HP     | 600%                 | EA  | 25       |

- Combination relay, overload, and capacitor
- Pre-wired for easy installation
- Extra-long compressor leads for mounting flexibility
- All models adapt to 115-volt compressors with external overload protector

| CAT. NO. | COMPRESSOR SIZES  | VOLTS | UOM | CASE QTY |
|----------|-------------------|-------|-----|----------|
| TOS21    | 1/2HP             | 115   | EA  | 20       |
| TOS41    | 1/4HP AND 1/3HP   | 115   | EA  | 20       |
| TOS81    | 1/12HP THRU 1/5HP | 115   | EA  | 20       |



## TorQstart 3-N-1 Kit



48 Frame Motors