



TITAN PRO[®]

Motor Run Capacitors 370/440 VAC Round Metal Can



- 370/440 VAC
- Continuous run
- Single capacitance
- Round Metal Can
- UL & cUL Listed



CAT. NO.	PRIOR CAT. NO.	UF	DIAMETER (IN.)	HEIGHT (IN.)	CASE QTY
TRCF3	-	3	1.77	2.17	100
TRCF5	36-5R3744*	5	1.77	2.17	100
TRCF6	36-6R3744*	6	1.77	2.17	100
TRCF7.5	T37075R	7.5	1.77	2.17	100
TRCF10	36-10R3744*	10	1.77	2.17	100
TRCF12.5	36-12R3744*	12.5	1.77	2.17	100
TRCF15	36-15R3744*	15	1.77	2.56	100
TRCF17.5	36-17R3744*	17.5	1.77	2.76	100
TRCF20	36-20R3744*	20	1.77	2.95	100
TRCF25	36-25R3744*	25	1.97	2.95	100
TRCF30	36-30R3744*	30	1.97	3.35	100
TRCF35	36-35R3744*	35	1.97	3.54	50
TRCF40	36-40R3744*	40	1.97	3.94	100
TRCF45	36-45R3744*	45	1.97	4.33	50
TRCF50	36-50R3744*	50	1.97	4.72	50
TRCF55	36-55R3744*	55	1.97	4.92	50
TRCF60	36-60R3744*	60	2.17	4.53	50
TRCF70	36-70R3744*	70	2.17	4.92	100
TRCF80	36-80R3744*	80	2.50	4.72	50
TRCF100	36-100R3744*	110	2.50	5.31	50

* PRIOR CATALOG NUMBERS IN RED ARE AVAILABLE WHILE SUPPLIES LAST

TITAN PRO[®]

Motor Run Capacitors 70/440 VAC Oval Metal Can



- 370/440 VAC
- Continuous run
- Single capacitance
- Oval Metal Can
- UL & cUL Listed

CAT. NO.	PRIOR CAT. NO.	UF	UOM	ORDER MULTIPLE
36-5J370	T37050H	5	EA	1
36-7.5J370	T37075H	7.5	EA	1
36-10J370	T37100H	10	EA	1
36-15K370	T37150H	15	EA	1

Motor Run Capacitors - 370 VAC Oval Metal Can

TITAN HD[®]

Run Capacitors Made in the U.S.A.



- Manufactured to EIA-456A standards
- Up to 60,000 hours operational life
- Aluminum cans filled with soybean based oil
- UL-801 fault current protection
- RoHS compliant
- Approval certifications: UL, cUL, IEC 60252
- Made in USA

CAT. NO.	PRIOR CAT. NO.	UF	DEPTH (IN.)	WIDTH (IN.)	HEIGHT (IN.)	CASE QTY
TOCF3	36-3-370440*	3	1.24	2.03	2.17	100
TOCF4	36-4-370440*	4	1.24	2.03	2.17	100
TOCF5	36-5-370440*	5	1.24	2.03	2.17	100
TOCF6	36-6-370440*	6	1.24	2.03	2.56	100
TOCF7.5	36-7-370440*	7.5	1.24	2.03	2.17	100
TOCF10	36-10-370440*	10	1.24	2.03	2.56	100
TOCF12.5	36-12-370440*	12.5	1.24	2.03	2.95	100
TOCF15	36-15-370440*	15	1.24	2.03	2.95	100
TOCF17.5	36-17-370440*	17.5	1.24	2.03	3.74	100
TOCF20	36-20-370440*	20	1.77	2.80	2.68	100
TOCF25	36-25-370440*	25	1.77	2.80	3.07	100
TOCF30	36-30-370440*	30	1.77	2.80	3.46	50
TOCF35	36-35-370440*	35	1.77	2.80	3.86	50
TOCF40	36-40-370440*	40	1.77	2.80	4.06	50
TOCF45	36-45-370440*	45	1.77	2.80	4.45	50
TOCF50	36-50-370440*	50	1.77	2.80	4.84	50
-	36-60-370440*	60	1.85	2.8	4.89	50

* PRIOR CATALOG NUMBERS IN RED ARE AVAILABLE WHILE SUPPLIES LAST

CAT. NO.	PRIOR CAT. NO.	VOLTAGE	UF	DEPTH (IN.)	WIDTH (IN.)	HEIGHT (IN.)	CASE QTY
TPOCF5A	T45050HU	370V/440V	5	1.25	2.00	1.56	50
TPOCF7.5A	T45075HU	370V/440V	7.5	1.25	2.00	2.19	50
TPOCF10A	T45100HU	370V/440V	10	1.25	2.00	2.88	50
TPOCF12.5A	T45125HU	370V/440V	12.5	1.25	2.00	2.88	50
TPOCF15A	T45150HU	370V/440V	15	1.25	2.00	2.88	50
TPOCF20A	T45200HU	370V/440V	20	1.25	2.00	2.88	50
TPOCF25B	T45250HU	370V/440V	25	1.25	2.00	2.88	50
TPOCF30A	T45300HU	370V/440V	30	1.25	2.00	3.88	50
TPOCF35A	T45350HU	370V/440V	35	1.25	2.00	3.88	50
TPOCF40A	T45400HU	370V/440V	40	1.75	2.75	2.91	50
TPOCF45A	T45450HU	370V/440V	45	1.75	2.75	2.91	50
TPOCF50A	T45500HU	370V/440V	50	1.75	2.75	2.91	50
TPOCF60A	T45600HU	370V/440V	60	1.75	2.75	3.91	50
TPOCF70A	T45700HU	370V/440V	70	1.75	2.75	3.91	50
TPOCF80A	T45800HU	370V/440V	80	1.75	2.75	3.91	50