

# TITAN PRO®

## Motor Run Capacitors - Dual Capacitance 370/440 VAC



CAT. NO.	PRIOR CAT. NO.	UF	DIAMETER (IN.)	HEIGHT (IN.)	CASE QTY
TRCFD205	36-205R3744	20+5	1.97	3.74	50
TRCFD2015	-	20+15	1.97	3.94	50
TRCFD255	36-255R3744*	25+5	1.97	3.54	50
TRCFD2575	-	25+7.5	1.97	3.74	50
TRCFD2515	-	25+15	1.97	4.33	50
TRCFD303	T3GR0330	30+3	1.97	4.33	50
TRCFD305	36-305R3744	30+5	1.97	3.94	50
TRCFD3075	T3GR7530	30+7.5	1.97	4.13	50
TRCFD353	T3GR0335	35+3	2.50	3.74	50
TRCFD354	36-354R3744*	35+4	1.97	4.53	50
TRCFD355	36-355R3744*	35+5	1.97	4.13	50
TRCFD3575	-	35+7.5	2.36	3.54	50
TRCFD403	T3GR0340	40+3	2.50	3.74	50
TRCFD405	36-405R3744*	40+5	2.36	3.54	50
TRCFD4075	36-407R3744*	40+7.5	2.50	3.74	50
TRCFD453	-	45+3	2.50	3.74	50
TRCFD455	36-455R3744*	45+5	2.50	3.74	50
TRCFD4575	-	45+7.5	2.50	3.74	50

CAT. NO.	PRIOR CAT. NO.	UF	DIAMETER (IN.)	HEIGHT (IN.)	CASE QTY
TRCFD4510	-	45+10	2.50	3.74	50
TRCFD503	-	50+3	2.50	3.74	50
TRCFD505	36-505R3744*	50+5	2.50	3.74	50
TRCFD5075	-	50+7.5	2.50	3.74	50
TRCFD50125	-	50+12.5	2.50	3.74	50
TRCFD553	-	55+3	2.50	3.74	50
TRCFD555	36-555R3744*	55+5	2.50	3.74	50
TRCFD5575	36-557R3744*	55+7.5	2.50	3.74	50
TRCFD603	-	60+3	2.50	3.74	50
TRCFD605	36-605R3744*	60+5	2.50	3.74	50
TRCFD6075	36-607R3744*	60+7.5	2.50	3.74	50
TRCFD6010	-	60+10	2.50	3.74	50
TRCFD705	T3GR0570	70+5	2.50	3.74	50
TRCFD7075	-	70+7.5	2.50	3.74	50
TRCFD805	36-805R3744	*80+5	2.50	3.74	50
TRCFD8075	T3GR7580	80+7.5	2.50	3.74	50
TRCFD8010	T3GR1080	80+10	2.50	3.74	50



- 370/440 VAC
- Continuous run
- Dual Capacitance
- Round Metal can
- Designed for continuous run
- UL & cUL Listed

\* PRIOR CATALOG NUMBERS IN RED ARE AVAILABLE WHILE SUPPLIES LAST

\* PRIOR CATALOG NUMBERS IN RED ARE AVAILABLE WHILE SUPPLIES LAST

# TITAN PRO®

## Run Capacitors - Dual Capacitance 370/440 VAC

- 370 & 440 VAC
- Continuous run
- Dual capacitance
- Oval Metal can
- UL & cUL Listed



# TITAN HD®

## Run Capacitors - Dual Cap. Made in the U.S.A.

- Manufactured to EIA-456A standards
- Up to 60,000 hours operational life
- Aluminum cans filled with soybean based oil
- UL-801 fault current protection
- RoHS compliant
- Approval certifications: UL, cUL, IEC 60252
- Made in USA



CAT. NO.	PRIOR CAT. NO.	UF	DEPTH (IN.)	WIDTH (IN.)	HEIGHT (IN.)	CASE QTY
TOCFD154	-	15+4	1.77	2.68	2.68	50
TOCFD155	36-15-5-3744*	15+5	1.77	2.68	2.68	100
TOCFD2015	-	20+15	1.77	2.80	3.86	50
TOCFD255	-	25+5	1.77	2.80	3.46	50
TOCFD2575	-	25+7.5	1.77	2.80	3.46	50
TOCFD2510	-	25+10	1.77	2.80	3.86	50
TOCFD304	-	30+4	1.77	2.80	3.86	50
TOCFD305	36-30-5-3744*	30+5	1.77	2.80	3.86	50
TOCFD3075	T3GJ7530	30+7.5	1.77	2.80	3.86	50
TOCFD353	-	35+3	1.77	2.80	4.25	50
TOCFD354	-	35+4	1.77	2.80	4.25	50
TOCFD355	36-35-5-3744*	35+5	1.77	2.80	4.25	50
TOCFD3575	T3GJ7535	35+7.5	1.77	2.80	4.25	50
TOCFD405	36-40-5-3744*	40+5	1.77	2.80	4.65	50
TOCFD4075	-	40+7.5	1.87	3.54	3.78	50
TOCFD455	36-45-5-3744*	45+5	1.77	2.80	5.04	50
TOCFD505	-	50+5	1.87	3.54	4.37	50
TOCFD555	T3GJ0555	55+5	1.87	3.54	4.57	50
TOCFD5510	-	55+10	1.87	3.54	5.16	50
TOCFD605	-	60+5	1.87	3.54	5.55	50

\* PRIOR CATALOG NUMBERS IN RED ARE AVAILABLE WHILE SUPPLIES LAST

CAT. NO.	PRIOR CAT. NO.	VOLTAGE	UF	DIAMETER (IN.)	HEIGHT (IN.)	CASE QTY
TPRCFD255A	T4JR0525U	370V/440V	25+5	2.00	2.91	50
TPRCFD305A	T4JR0530U	370V/440V	30+5	2.00	2.91	50
TPRCFD3075A	T4JR7530U	370V/440V	30+7.5	2.00	2.91	50
TPRCFD355A	T4JR0535U	370V/440V	35+5	2.00	3.84	50
TPRCFD3575A	T4JR7535U	370V/440V	35+7.5	2.00	3.84	50
TPRCFD405A	T4JR0540U	370V/440V	40+5	2.00	3.84	50
TPRCFD4075A	T4JR7540U	370V/440V	40+7.5	2.00	3.84	50
TPRCFD455A	T4JR0545U	370V/440V	45+5	2.00	3.84	50
TPRCFD4575A	T4JR7545U	370V/440V	45+7.5	2.00	3.84	50
TPRCFD505A	T4JR0550U	370V/440V	50+5	2.00	3.84	50
TPRCFD5075A	T4JR7550U	370V/440V	50+7.5	2.00	3.84	50
TPRCFD5575A	T4JR7555U	370V/440V	55+7.5	2.50	2.91	50
TPRCFD605A	T4JR0560U	370V/440V	60+5	2.50	2.91	50
TPRCFD6075A	T4JR7560U	370V/440V	60+7.5	2.50	2.91	50
TPRCFD805A	T4JR0580U	370V/440V	80+5	2.50	3.91	50