



TITAN PRO[®]

Motor Start Capacitors 110/125 VAC



- Dry Electrolytic Non Polarized Capacitor
- -40 to 70 Degrees Celsius Rating
- Rated for 3 Second Start
- 20 Starts per Hour
- 110-125 VAC
- UL and cUL Recognized



CAT. NO.	PRIOR CAT#	UF	DIAMETER (IN.)	HEIGHT (IN.)	CASE QTY
TMJ25	35-25A125*	25-30	1-7/16"	2-3/4"	100
TMJ30	35-30A125*	30-36	1-7/16"	2-3/4"	100
TMJ36	35-36A125	36-43	1-7/16"	2-3/4"	100
TMJ43	35-43A125*	43-53	1-7/16"	2-3/4"	100
TMJ64	35-64A125*	64-77	1-7/16"	2-3/4"	100
TMJ72	35-72A125*	72-88	1-7/16"	2-3/4"	100
TMJ88	35-88A125*	88-108	1-7/16"	2-3/4"	100
TMJ108	35-108A125*	108-130	1-7/16"	2-3/4"	100
TMJ124	35-124A125*	124-149	1-7/16"	2-3/4"	100
TMJ130	35-130A125*	130-156	1-7/16"	2-3/4"	100
TMJ145	35-145A125*	145-174	1-7/16"	2-3/4"	100
TMJ161	35-161A125*	161-193	1-7/16"	2-3/4"	100
TMJ189	35-189A125*	189-227	1-7/16"	2-3/4"	100
TMJ200	35-200A125*	200-240	1-7/16"	2-3/4"	100
TMJ216	35-216A125*	216-259	1-7/16"	2-3/4"	100
TMJ233	35-233A125*	233-280	1-7/16"	2-3/4"	100
TMJ243	35-243A125*	243-292	1-7/16"	2-3/4"	100
TMJ270	35-270A125*	270-324	1-7/16"	2-3/4"	100
TMJ295	35-295A125*	295-354	1-7/16"	2-3/4"	100
TMJ300	35-300A125*	300-360	1-7/16"	4-3/8"	100
TMJ324	35-324A125*	324-388	1-7/16"	2-3/4"	100
TMJ340	35-340D125*	340-408	1-7/16"	3-3/8"	100
TMJ378A	35-378D125*	378-455	1-13/16"	3-3/8"	50
TMJ400	35-400B125*	400-480	1-7/16"	3-3/8"	100
TMJ430	35-430D125*	430-516	1-7/16"	3-3/8"	100
TMJ460	35-460D125*	460-552	1-7/16"	3-3/8"	100
TMJ540A	35-540D125*	540-648	1-13/16"	3-3/8"	50
TMJ590A	35-590D125*	590-708	1-13/16"	3-3/8"	50
TMJ645	35-645E125*	645-774	1-13/16"	4-3/8"	50
TMJ708	35-708E125*	708-850	1-13/16"	4-3/8"	50
TMJ829	35-829E125*	829-995	1-13/16"	4-3/8"	50

* PRIOR CATALOG NUMBERS IN RED ARE AVAILABLE WHILE SUPPLIES LAST

TITAN PRO[®]

Motor Start Capacitors 220/250 VAC



- Dry Electrolytic Non Polarized Capacitor
- -40 to 70 Degrees Celsius Rating
- Rated for 3 Second Start
- 20 Starts per Hour
- 220-250 VAC
- UL and cUL Recognized



CAT. NO.	PRIOR CAT#	UF	DIAMETER (IN.)	HEIGHT (IN.)	CASE QTY
TTMJ21	35-21A250*	21-25	1-7/16"	2-3/4"	100
TTMJ25	35-25A250*	25-30	1-7/16"	2-3/4"	100
TTMJ30	35-30A250*	30-36	1-7/16"	2-3/4"	100
TTMJ36	35-36B250*	36-43	1-7/16"	2-3/4"	100
TTMJ43	35-43B250*	43-53	1-7/16"	2-3/4"	50
TTMJ53	35-53A250*	53-64	1-7/16"	3-3/8"	100
TTMJ64	35-64A250*	64-77	1-7/16"	2-3/4"	100
TTMJ72	35-72D250*	72-88	1-13/16"	3-3/8"	50
TTMJ88	35-88D250*	88-108	1-13/16"	3-3/8"	50
TTMJ108	35-108D250*	108-130	1-13/16"	3-3/8"	50
TTMJ124	35-124D250*	124-149	1-13/16"	4-3/8"	50
TTMJ145	35-145F250*	145-174	1-13/16"	3-3/8"	50
TTMJ189	35-189G250*	189-227	2-1/16"	4-3/8"	50
TTMJ216	35-216F250*	216-259	2-1/16"	3-3/8"	50
TTMJ243	35-243G250*	243-292	2-1/16"	3-3/8"	50
TTMJ270	35-270G250*	270-324	2-1/16"	3-3/8"	50
TTMJ320	35-320H250*	320-384	2-1/16"	4-3/8"	50
TTMJ378	35-378H250*	378-455	2-9/16"	4-3/8"	50
TTMJ400	35-400H250*	400-480	2-1/16"	4-3/8"	50

* PRIOR CATALOG NUMBERS IN RED ARE AVAILABLE WHILE SUPPLIES LAST

TITAN PRO[®]

Motor Start Capacitors 330 VAC



- Start Motor Capacitor
- 330 VAC
- 50/60 Hertz
- Standard Blade Terminals
- -40 to 70 Degrees Celsius Rating
- Rated for 3 Second Start
- 20 Starts per Hour
- UL and cUL Recognized



CAT. NO.	PRIOR CAT#	UF	DIAMETER (IN.)	HEIGHT (IN.)	CASE QTY
TRMJ21	35-21B330*	21-25	1-7/16"	3-3/8"	100
TRMJ25	35-25B330*	25-30	1-7/16"	3-3/8"	100
TRMJ30	35-30D330*	30-36	1-7/16"	3-3/8"	100
TRMJ36	35-36D330*	36-43	1-7/16"	3-3/8"	50
TRMJ43	35-43D330*	43-53	1-13/16"	3-3/8"	50
TRMJ56	35-53D330*	53-64	1-13/16"	3-3/8"	50
TRMJ64	35-64D330*	64-77	1-13/16"	3-3/8"	50
TRMJ72	35-72E330*	72-88	1-13/16"	3-3/8"	50
TRMJ88	35-88F330*	88-108	2-1/16"	3-3/8"	50
TRMJ108	35-108G330*	108-130	2-1/16"	4-3/8"	50
TRMJ124	35-124G330*	124-149	2-1/16"	4-3/8"	50
TRMJ161	35-161H330*	161-193	2-1/16"	4-3/8"	50
TRMJ189	35-189G330*	189-227	2-1/16"	4-3/8"	50
TRMJ216	35-216H330*	216-259	2-9/16"	4-3/8"	25
TRMJ270	35-270H330*	270-324	2-9/16"	4-3/8"	25

* PRIOR CATALOG NUMBERS IN RED ARE AVAILABLE WHILE SUPPLIES LAST