



UL467 LISTED &
CSA C22.2 NO.41
SUITABLE FOR DIRECT BURIAL
& GROUNDING/BONDING

Copper C-Taps

- Applications Include Copper to Copper Tapping, Splicing or Stub/Pigtail
- High Strength Electrolytic Copper
- Allows for 2 Continuous Parallel Conductors
- Compact Size & Range Taking



FIG 1



FIG 2

DIMENSIONS = INCHES

DIMENSIONS = INCHES

CAT. NO.	FIG	DIE COLOR	CONDUCTOR RANGE			DIMENSIONS				BOX QTY
			RUN	TAP	STRIP L	L	W (ID)	H	T	
91802	1	RED	14	16-14	1/2	.32	.18	.16	.07	275
			12	16-12						
			10	14						
91803	1	BLUE	10	10	5/8	.61	.32	.36	.07	275
			8	12						
91804	1	GRAY	6	10-12	5/8	.61	.32	.43	.07	200
			8	8-10						
91805	1	BROWN	4	8-10-12	1-1/4	1.17	.41	.43	.07	150
			6	6-8						
91806	1	GREEN	4	6-4	1-1/4	1.17	.45	.52	.07	100
			3	12-6						
91807	1	PINK	4	4	1-1/4	1.17	.49	.54	.07	100
			3	4-6						
			2	12-6						
91808	1	BLACK	1	12-4	2	1.75	.53	.64	.07	100
			2	4-6						
			3	4-3						
91809	1	ORANGE	1/0	12-4	2	1.75	.61	.71	.09	50
			1	4-3						
			2	4-2						
91810	1	PURPLE	2/0	12-4	2	1.75	.69	.77	.09	30
			1/0	2						
			1	1-2						
91811	1	YELLOW	3/0	2-12	1	1.75	.81	1.07	.09	30
			2/0	1-2						
			1/0	1/0-1						

CAT. NO.	FIG	DIE COLOR	CONDUCTOR RANGE			DIMENSIONS				BOX QTY
			RUN	TAP	STRIP L	L	W (ID)	H	T	
91812	2	YELLOW	1	1	1	1.30	.79	.63	.16	50
			1/0	1/0-2						
			2/0	2/0-4						
			3/0	1/0-6						
91813	2	BLUE	4/0	1-8	1	1.46	.79	.79	.20	50
			2/0	2/0-1						
			3/0	3/0-3						
			4/0	4/0-4						
91814	2	BLUE	250	1/0-8	1-1/8	1.67	1.03	.85	.20	25
			2/0	2/0-1						
			3/0	3/0-3						
			4/0	4/0-4						
91815	2	BROWN	250	3/0-6	1-1/8	1.71	1.03	.90	.20	25
			300	2/0-8						
			4/0	4/0-2/0						
			250	250-1						
91816*	2	BROWN 600MCM BLACK 750MCM	300	4/0-4	1-5/16	1.87	1.28	1.02	.20	15
			350	3/0-6						
			400	3/0-2						
			450	250-4						
			500	250-6						
91817*	2	WHITE	350	350-4/0	1-5/16	2.17	1.29	1.18	.30	10
			400	400-2/0						
			450	450-1						
			500	500-2						
91818*	2	-	750-500	4/0-6	2-3/4	2.75	1.97	1.34	.16	5
			750	750-4/0						

*NOT LISTED FOR DIRECT BURIAL, GROUNDING OR BONDING



- Heavy Wall High Strength Electrolytic Copper
- Allows for 2 Continuous Parallel Conductors
- Range Taking

UL467 LISTED &
CSA C22.2 NO.41
SUITABLE FOR DIRECT BURIAL
& GROUNDING/BONDING



DIMENSIONS = INCHES

CAT. NO.	CONDUCTOR RANGE		DIE TYPE	DIMENSIONS					STRIP LENGTH	BOX QTY
	RUN MAX	TAP MAX		L (OD)	L (ID)	W	D	ENTRY		
91819	6-6	6-6	BG	.77	.46	.71	.43	.29	3/4	50
91820	6-4	4-4	BG	.81	.53	.63	.47	.31	3/4	25
91821	2-2	8-4	C	.98	.65	.75	.61	.37	3/4	50
91822	2-2	2-2	C	1.05	.76	.76	.60	.45	3/4	50
91823	1/0-2/0	1/0-2/0	C	1.35	.87	.95	.80	.43	1-1/8	25
91824	3/0-4/0	1/0-2/0	D3	1.64	1.01	1.07	.97	.60	1-1/4	15
91825	3/0-4/0	3/0-4/0	D3	1.58	1.10	1.07	.97	.56	1-1/4	15