

High Viscosity Regular Bodied 303 Series Clear Cements



- Regular Bodied Clear Cement for PVC pipe and fittings up to 4" diameter for Sch. 40 pipe & up to 2" for Sch. 80 with interference fit
- Recommended application temperature 40°F to 110°F
- Sets up Quickly
- Low-Voc Compliant, Meets ASTM-D2564

| CAT. NO. | SIZE | CASE QTY | WT/CASE |
|----------|---------|----------|---------|
| G30366S | 1/4 PT. | 24 | 9 |
| G30356S | 1/2 PT. | 24 | 16 |
| G30346S | 1 PT. | 24 | 27 |
| G30336S | 1 QT. | 12 | 26 |
| G30324 | 1 GAL. | 6 | 52 |

Medium Bodied 404 Series Clear Cements



- Medium Bodied Clear Cement for PVC pipe and fittings up to 6" diameter for Sch. 40 and Sch. 80
- Recommended application temperature 40°F to 110°F
- Low-Voc Compliant, Meets ASTM-D2564

| CAT. NO. | OLD CAT. NO. | SIZE | CASE QTY | WT/CASE |
|----------|--------------|---------|----------|---------|
| G31017 | G40466S | 1/4 PT. | 24 | 9 |
| G40456S | | 1/2 PT. | 24 | 16 |
| G40446S | | 1 PT. | 24 | 27 |
| G40436S | | 1 QT. | 12 | 26 |
| G1224 | G40424 | 1 GAL. | 6 | 52 |

High Viscosity Medium Bodied 403 Series Gray Cements



- Medium Bodied Gray Cement for PVC pipe and fittings up to 6" diameter for Sch. 40 and Sch. 80 Conduits
- Recommended application temperature 40°F to 110°F
- Low-Voc Compliant, Meets ASTM-D2564

| CAT. NO. | SIZE | CASE QTY | WT/CASE |
|----------|--------|----------|---------|
| G40336S | 1 QT. | 12 | 26 |
| G40324 | 1 GAL. | 6 | 52 |

Medium Bodied Gray Cement



- Fast setting gray cement solvent welds PVC, dauber included
- Medium viscosity easily fills gaps and provides more working time
- Can be used on all schedules and classes of PVC pipe and fittings up to 6" dia.
- Low-VOC Compliant
- Meets ASTM Standard D2564 and complies with NSF/ANSI 61

| CAT. NO. | SIZE | CASE QTY | WT/CASE |
|----------|-------|----------|---------|
| G30885 | 1 QT. | 24 | 28 |