





Voltage/Metal/Wood Stud Detector

- Finds wood, metal studs and joists behind walls, floors, and ceilings
- Stud Detection: 1-3/16" (±5/32")
- Stud Detection Depth: < 25/64"
- LCD Display
- AC Voltage Detection Range (Non Contact): 50-600VAC, 50-60Hz

CAT NO	NESCRIPTION	мпп	

MS6906 STUD DETECTOR



Heavy Duty Solenoid Voltage & Continuity Tester

- Test Voltage from 120V to 600V AC/DC
- Non-Contact Voltage Sensor from 90V to 1000V
- Test Continuity & Polarity
- Case serves as prod holder for one-hand operation
- Self-Storing prods
- Solenoid Sensing indicated by LEDs & Vibration
- Ergonomic Soft PVC housing for comfort grip
- LED Spotlight Illuminates Work Area
- Battery not Included (AAA x 1)

CAT. NO.	INNER BOX QTY	CASE QTY
59100	5	60

CE

- LED Light Meter
- High Precision 0-200,000 LUX (20,000 FC) ± 3% Range
- Auto & Manual Range Switching
- Inquiry Function for Max & Min Values
- Data Hold Function
- Peak Value Measurement
- Zero Calibration Function

CAT. NO.	MOQ
MS66I2T	1

- Relative Value Measurement
- 3-1/2" LCD Display
- FC/LUX Conversion Function
- Out-of-Range Indication
- Low Battery Indicator
- Touch Tone/Mute Function
- Auto Power Off



LED Light Meter



Digital Light Meter



- Easy-to-use, Pocket Size & Light Weight
- Low Battery Indicator
- Photo Detector: One Silicon Photo Diode with Filter
- Measuring Range: 0-1999 Lux = 1 Lux ±(5%+2) 2000-19990 Lux = $10 \text{ Lux } \pm (5\% + 2)$ $20000-50000 \text{ Lux} = 100 \text{ Lux} \pm (5\%+2)$
- Lead Lenoth: 5FT
- Includes One (1) 9 Volt Battery & User Manual
- Photo Detector Dimensions: 3.2" X 2.0" X 0.8"
- Product Dimensions: 5.0" X 2.8" X 1.0"
- Weight: 6.4 Oz

CAT. NO.	DESCRIPTION	MOQ	
MS6610	DIGITAL LIGHT METER	1	