



## Motor Start Capacitors 110/125 VAC



- 3• Dry Electrolytic Non Polarized Capacitor
- -40 to 70 Degrees Celsius Rating
- Rated for 3 Second Start
- 20 Starts per Hour
- 110-125 VAC
- UL and cUL Recognized



CAT. NO.	PRIOR CAT#	UF	DIAMETER (IN.)	HEIGHT (IN.)	CASE QTY
TMJ25	35-25A125*	25-30	1-7/16"	2-3/4"	100
TMJ30	35-30A125*	30-36	1-7/16"	2-3/4"	100
TMJ36	35-36A125	36-43	1-7/16"	2-3/4"	100
TMJ43	35-43A125*	43-53	1-7/16"	2-3/4"	100
TMJ64	35-64A125*	64-77	1-7/16"	2-3/4"	100
TMJ72	35-72A125*	72-88	1-7/16"	2-3/4"	100
TMJ88	35-88A125*	88-108	1-7/16"	2-3/4"	100
TMJ108	35-108A125*	108-130	1-7/16"	2-3/4"	100
TMJ124	35-124A125*	124-149	1-7/16"	2-3/4"	100
TMJ130	35-130A125*	130-156	1-7/16"	2-3/4"	100
TMJ145	35-145A125*	145-174	1-7/16"	2-3/4"	100
TMJ161	35-161A125*	161-193	1-7/16"	2-3/4"	100
TMJ189	35-189A125*	189-227	1-7/16"	2-3/4"	100
TMJ200	35-200A125*	200-240	1-7/16"	2-3/4"	100
TMJ216	35-216A125*	216-259	1-7/16"	2-3/4"	100
TMJ233	35-233A125*	233-280	1-7/16"	2-3/4"	100
TMJ243	35-243A125*	243-292	1-7/16"	2-3/4"	100
TMJ270	35-270A125*	270-324	1-7/16"	2-3/4"	100
TMJ295	35-295A125*	295-354	1-7/16"	2-3/4"	100
TMJ300	35-300A125*	300-360	1-7/16"	4-3/8"	100
TMJ324	35-324A125*	324-388	1-7/16"	2-3/4"	100
TMJ340	35-340D125*	340-408	1-7/16"	3-3/8"	100
TMJ378A	35-378D125*	378-455	1-13/16"	3-3/8"	50
TMJ400	35-400B125*	400-480	1-7/16"	3-3/8"	100
TMJ430	35-430D125*	430-516	1-7/16"	3-3/8"	100
TMJ460	35-460D125*	460-552	1-7/16"	3-3/8"	100
TMJ540A	35-540D125*	540-648	1-13/16"	3-3/8"	50
TMJ590A	35-590D125*	590-708	1-13/16"	3-3/8"	50
TMJ645	35-645E125*	645-774	1-13/16"	4-3/8"	50
TMJ708	35-708E125*	708-850	1-13/16"	4-3/8"	50
TMJ829	35-829E125*	829-995	1-13/16"	4-3/8"	50

\* PRIOR CATALOG NUMBERS IN RED ARE AVAILABLE WHILE SUPPLIES LAST